



221 Remington Fireball

.224"	22
Weight (grains)	Spitzer SP
Ballistic Coefficient	45
Sectional Density	0.143
COAL Tested	0.128
Speer Part No.	1.830"
	1023

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Remington	CCI 400	17.3	2603	18.3	2775
Alliant 2400	Remington	CCI 400	14.0	2599	15.0	2762
Hodgdon H110	Remington	CCI 450	13.0	2555	14.0	2757
IMR 4198	Remington	CCI 400	16.8	2556	17.8 C	2731
IMR 4227	Remington	CCI 400	15.2	2571	16.2	2727

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load