



221 Remington Fireball

.224"	22	22
	HP	Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.148	0.148
COAL Tested	1.830"	1.830"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant 2400	Remington	CCI 400	13.3	2411	14.3	2607
Alliant Reloder 7	Remington	CCI 400	16.7	2441	17.7	2606
IMR 4227	Remington	CCI 400	14.7	2404	15.7	2585
IMR 4198	Remington	CCI 400	16.0	2330	17.0	2527
Hodgdon H110	Remington	CCI 450	12.2	2268	13.2	2465

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load