



223 Remington (Handgun)

.224"	22
	Spitzer
	SP
Weight (grains)	45
Ballistic Coefficient	0.143
Sectional Density	0.128
COAL Tested	2.155"
Speer Part No.	1023

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 3031	IMI	CCI 400	25.0	2712	27.0 C	3121
Winchester 748	IMI	CCI 450	26.5	2858	28.5 C	3097
Vihtavuori N133	IMI	CCI 400	22.5	2789	24.5	3065
IMR 4198	IMI	CCI 400	21.0	2782	23.0	3061
Hodgdon H322	IMI	CCI 400	24.0	2713	26.0	3029
IMR 4895	IMI	CCI 400	25.0	2701	27.0 C	3022
Accurate 2015	IMI	CCI 400	23.0	2760	25.0	3010
Accurate 2460	IMI	CCI 450	24.0	2683	26.0	2967
Alliant Reloder 7	IMI	CCI 400	18.0	2564	20.0	2636

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load