



223 Remington (Handgun)

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	55	55
Ballistic Coefficient	0.212	0.233
Sectional Density	0.157	0.157
COAL Tested	2.175"	2.175"
Speer Part No.	1047	1032

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2520	IMI	CCI 450	25.0	2827	27.0	3008
Hodgdon H4895	IMI	CCI 400	23.5	2595	25.5	2983
Winchester 748	IMI	CCI 450	26.0	2735	28.0	2964
IMR 3031	IMI	CCI 400	24.0	2574	26.0	2962
IMR 4895	IMI	CCI 400	24.5	2621	26.5	2932
Vihtavuori N133	IMI	CCI 400	21.5	2593	23.5	2849
Hodgdon H322	IMI	CCI 400	22.5	2501	24.5	2792
Accurate 2015	IMI	CCI 400	21.5	2535	23.5	2765
IMR 4198	IMI	CCI 400	19.0	2473	21.0	2721

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load