



## 30-30 Winchester (Handgun)

<b>.308"</b>	<b>30 Varminter HP</b>
<b>Weight (grains)</b>	110
<b>Ballistic Coefficient</b>	0.128
<b>Sectional Density</b>	0.166
<b>COAL Tested</b>	2.415"
<b>Speer Part No.</b>	1835

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	30.0	2356	<b>34.0</b>	2618
Hodgdon H322	Winchester	CCI 200	31.0	2003	<b>35.0</b>	2373
Winchester 748	Winchester	CCI 250	36.0	2111	<b>40.0 C</b>	2343
Accurate 2015	Winchester	CCI 200	30.0	1974	<b>34.0</b>	2340
IMR 4064	Winchester	CCI 200	33.0	1912	<b>37.0 C</b>	2266
IMR 4895	Winchester	CCI 200	31.0	1884	<b>35.0</b>	2206
Hodgdon H4895	Winchester	CCI 200	30.0	1853	<b>34.0</b>	2165
Vihtavuori N133	Winchester	CCI 200	27.0	1817	<b>31.0</b>	2153

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*