



30-30 Winchester (Handgun)

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	2.550"	2.700"	2.700"	2.700"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	Winchester	CCI 250	33.0	1956	37.0	2171
Alliant Reloder 7	Winchester	CCI 200	25.0	1931	29.0	2144
Hodgdon H322	Winchester	CCI 200	27.0	1780	31.0	2110
Vihtavuori N140	Winchester	CCI 200	30.0	1847	34.0	2078
Accurate 2520	Winchester	CCI 250	31.0	1853	35.0	2066
Hodgdon H335	Winchester	CCI 250	28.0	1841	32.0	2024
Hodgdon Varget	Winchester	CCI 200	29.0	1776	33.0	2009
Alliant Reloder 10X	Winchester	CCI 200	24.0	1732	28.0	1960
IMR 4895	Winchester	CCI 200	27.0	1669	31.0	1955
IMR 4198	Winchester	CCI 200	24.0	1287	26.0	1458

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load