



30 Carbine (Handgun)

.308"	30
	Plinker® SPRN
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	1.620"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	IMI Commercial	CCI 450	14.5	1475	15.5	1589
Winchester 296	IMI Commercial	CCI 450	14.5	1415	15.5	1527
Alliant 2400	IMI Commercial	CCI 400	11.7	1385	12.7	1476
IMR 4227	IMI Commercial	CCI 400	13.5	1312	14.5	1417
Vihtavuori N110	IMI Commercial	CCI 400	12.0	1306	13.0 C	1394
IMR 4198	IMI Commercial	CCI 400	14.5	1116	15.5 C	1201
Alliant Unique	IMI Commercial	CCI 400	4.5	938	5.5	1142
Accurate 1680	IMI Commercial	CCI 400	15.0	1077	16.0 C	1126

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load