



32-20 Winchester (Contender Only)

.308"	30 Varminter HP	30 Carbine TMJ® RN
Weight (grains)	110	110
Ballistic Coefficient	0.128	0.179
Sectional Density	0.166	0.166
COAL Tested	1.710"	1.710"
Speer Part No.	1835	1846

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 500	15.0	1598	16.0	1813
Winchester 296	Winchester	CCI 500	14.5	1610	15.5	1765
Accurate No. 9	Winchester	CCI 500	12.5	1579	13.5	1739
IMR 4227	Winchester	CCI 500	15.0	1540	16.0	1730
Alliant 2400	Winchester	CCI 500	11.0	1371	12.0	1594
IMR 4198	Winchester	CCI 500	16.0	1375	17.0 C	1576
IMR SR 4759	Winchester	CCI 500	12.0	1279	13.0 C	1566
Alliant Herco	Winchester	CCI 500	7.4	1472	8.4	1552
Hodgdon HS-6	Winchester	CCI 500	8.1	1484	9.1	1539

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load