



## 357 Magnum

.358"	38	38
	LSWC	LSWC HP
Weight (grains)	158	158
Ballistic Coefficient	0.123	0.121
Sectional Density	0.176	0.176
COAL Tested	1.570"	1.575"
Speer Part No.	4624	4628

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Speer	CCI 500	5.5	970	<b>6.0</b>	1034
IMR SR 7625	Speer	CCI 500	4.8	926	<b>5.3</b>	1021
Hodgdon Hi-Skor 700-X	Speer	CCI 500	4.5	904	<b>5.0</b>	1002
Winchester 231	Speer	CCI 500	4.9	897	<b>5.4</b>	989
Alliant Bullseye	Speer	CCI 500	4.3	848	<b>4.8</b>	939
Hodgdon HP-38	Speer	CCI 500	4.5	839	<b>5.0</b>	932

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*