



35 Remington (Handgun)

	35
	SPFN Hot-Cor®
Weight (grains)	180
Ballistic Coefficient	0.236
Sectional Density	0.201
COAL Tested	2.315"
Speer Part No.	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Winchester	CCI 200	36.0	1871	38.0	2023
Hodgdon H322	Winchester	CCI 200	36.0	1825	38.0	1997
IMR 4895	Winchester	CCI 200	38.0	1786	40.0	1896
Hodgdon BL-C(2)	Winchester	CCI 250	33.0	1736	35.0	1885
Winchester 748	Winchester	CCI 250	40.0	1714	42.0	1879
IMR 3031	Winchester	CCI 200	36.0	1734	38.0	1837
IMR 4198	Winchester	CCI 200	28.0	1683	30.0	1806
Hodgdon H380	Winchester	CCI 250	42.0	1653	44.0	1782
Alliant Reloder 7	Winchester	CCI 200	28.0	2565	30.0	1739

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load