



## 35 Remington (Handgun)

<b>.358"</b>	<b>35</b>
<b>Weight (grains)</b>	<b>SPFN Hot-Cor®</b>
<b>Ballistic Coefficient</b>	220
<b>Sectional Density</b>	0.286
<b>COAL Tested</b>	0.245
<b>Speer Part No.</b>	2.470"
	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>IMR 4064</b>	Winchester	CCI 200	34.0	1558	<b>36.0</b>	1638
<b>Hodgdon H414</b>	Winchester	CCI 250	38.0	1550	<b>40.0</b>	1626
<b>IMR 4895</b>	Winchester	CCI 200	33.5	1539	<b>35.5</b>	1620
<b>IMR 3031</b>	Winchester	CCI 200	31.5	1495	<b>33.5</b>	1611
<b>Hodgdon H335</b>	Winchester	CCI 200	30.0	1429	<b>32.0</b>	1567
<b>Hodgdon BL-C(2)</b>	Winchester	CCI 250	33.0	1460	<b>35.0</b>	1561
<b>Winchester 748</b>	Winchester	CCI 250	33.0	1438	<b>35.0</b>	1550
<b>Alliant Reloder 7</b>	Winchester	CCI 200	22.5	1243	<b>24.5</b>	1421

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*