



38 S&W

0.357"	38 JHP	38 TMJ® FN
Weight (grains)	125	125
Ballistic Coefficient	0.129	0.146
Sectional Density	0.140	0.140
COAL Tested	1.055"	1.055"
Speer Part No.	4013	4015

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Herco	Winchester	CCI 500	4.7	914	5.0	986
Alliant Unique	Winchester	CCI 500	4.5	920	4.8	972
Alliant Red Dot	Winchester	CCI 500	3.0	773	3.3	846
IMR SR 7625	Winchester	CCI 500	3.2	748	3.5	826
Alliant Bullseye	Winchester	CCI 500	2.8	742	3.0	789
Winchester 231	Winchester	CCI 500	DNR	—	3.0	662

DNR — Do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load