



38 Special

.357"	38 UCHP	38 GDHP SB
Weight (grains)	110	110
Ballistic Coefficient	0.113	0.117
Sectional Density	0.123	0.123
COAL Tested	1.455"	1.455"
Speer Part No.	4007	4009

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pistol	Speer	CCI 500	6.2	1006	6.6	1074
Vihtavuori 3N37	Speer	CCI 500	6.5	990	6.9	1071
Alliant Unique	Speer	CCI 500	5.4	947	5.8	1065
Accurate No. 5	Speer	CCI 500	6.8	979	7.2	1043
Hodgdon TITEGROUP	Speer	CCI 500	4.1	890	4.5	1002
Hodgdon H. Universal	Speer	CCI 500	5.1	829	5.5	998
Hodgdon Hi-Skor 700-X	Speer	CCI 500	4.2	907	4.6	997
Alliant Bullseye	Speer	CCI 500	4.2	891	4.6	990
Winchester 231	Speer	CCI 500	4.6	871	5.0	971
Alliant American Select	Speer	CCI 500	DNR	—	4.3	887

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load