



45 Automatic

.451"	45
	TMJ® Match
	SWC
Weight (grains)	185
Ballistic Coefficient	0.090
Sectional Density	0.130
COAL Tested	1.275"
Speer Part No.	4473

NOTE: These loads are not necessarily at maximum pressure. They are held to velocities popular for target shooting.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 5	Speer	CCI 300	7.2	764	8.0	859
Alliant Red Dot	Speer	CCI 300	4.5	767	4.9	829
Alliant Unique	Speer	CCI 300	5.0	652	5.8	829
Alliant Bullseye	Speer	CCI 300	4.5	727	4.9	790
Hodgdon Hi-Skor 700-X	Speer	CCI 300	4.3	701	4.7	788
IMR PB	Speer	CCI 300	5.0	719	5.5	770
Hodgdon HP-38	Speer	CCI 300	4.9	668	5.4	759
Winchester 231	Speer	CCI 300	5.0	669	5.5	752
IMR SR 7625	Speer	CCI 300	5.1	615	5.6	717

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load