



45 Colt

.452"	45
Weight (grains)	LSWC
Ballistic Coefficient	200
Sectional Density	0.078
COAL Tested	0.140
Speer Part No.	1.515"
	4678

NOTE: Firmly roll-crimp over the bullet shoulder for reliable performance.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Unique	Winchester	CCI 300	8.0	896	9.5	1061
Hodgdon HS-6	Winchester	CCI 300	10.7	898	12.2	1036
Alliant Herco	Winchester	CCI 300	8.0	855	9.5	1021
Alliant Red Dot	Winchester	CCI 300	6.3	859	7.3	1001
Winchester 231	Winchester	CCI 300	7.3	854	8.3	998
Alliant Bullseye	Winchester	CCI 300	6.5	835	7.5	988
Alliant Green Dot	Winchester	CCI 300	7.3	834	8.3	980
IMR SR 7625	Winchester	CCI 300	7.1	860	8.1	959
Hodgdon Hi-Skor 700-X	Winchester	CCI 300	5.9	795	6.9	959

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load