



## 45 Colt (Ruger and Contender Only)

<b>.452"</b>	<b>45</b>
<b>Weight (grains)</b>	<b>GDHP</b>
<b>Ballistic Coefficient</b>	250
<b>Sectional Density</b>	0.165
<b>COAL Tested</b>	0.175
<b>Speer Part No.</b>	1.600"
	4484

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Winchester 296</b>	Winchester	CCI 350	19.0	1118	<b>21.0</b>	1203
<b>Hodgdon H110</b>	Winchester	CCI 350	19.0	1091	<b>21.0</b>	1200
<b>Accurate No. 9</b>	Winchester	CCI 350	16.0	1052	<b>18.0</b>	1182
<b>Vihtavuori N110</b>	Winchester	CCI 300	18.0	1003	<b>20.0</b>	1148
<b>Alliant 2400</b>	Winchester	CCI 300	18.0	1058	<b>20.0</b>	1145
<b>Alliant Power Pistol</b>	Winchester	CCI 300	11.0	1039	<b>12.0</b>	1112
<b>Vihtavuori N350</b>	Winchester	CCI 300	11.0	973	<b>12.0</b>	1105
<b>Alliant Unique</b>	Winchester	CCI 300	9.8	995	<b>10.8</b>	1075

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*