



## 45 Colt (Ruger and Contender Only)

<b>.451"</b>	<b>45</b>
<b>Weight (grains)</b>	<b>JSP</b>
<b>Ballistic Coefficient</b>	300
<b>Sectional Density</b>	0.199
<b>COAL Tested</b>	0.211
<b>Speer Part No.</b>	1.640"
	4485

NOTE: Seat bullet to REAR cannelure and use a neckdown crimp.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 296	Winchester	CCI 350	20.7	1084	<b>23.0</b>	1193
Hodgdon H110	Winchester	CCI 350	21.1	974	<b>23.5</b>	1156
Alliant 2400	Winchester	CCI 300	15.8	938	<b>17.5</b>	1048
Accurate No. 9	Winchester	CCI 350	15.0	959	<b>15.5</b>	1041
† IMR SR 4759	Winchester	CCI 300	20.3	825	<b>22.5</b>	1029

† —DO NOT confuse with SR 4756 or excessive pressure will result.

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load