

50 Action Express

.500"	50 JHP
Weight (grains)	325
Ballistic Coefficient	0.169
Sectional Density	0.186
COAL Tested	1.575"
Speer Part No.	4495

REVOLVER VELOCITIES Freedom Arms M555 7.5"

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Speer	CCI 350	29.4	1324	32.6	1475
Winchester 296	Speer	CCI 350	29.5	1321	32.7	1461
Alliant 2400	Speer	CCI 300	26.0	1345	28.0	1461
Vihtavuori N110	Speer	CCI 300	25.0	1283	27.0	1444
Accurate 1680	Speer	CCI 350	34.0	1243	37.8 C	1374
IMR 4227	Speer	CCI 350	29.5	1256	31.1	1344
Accurate No. 9	Speer	CCI 350	22.6	1270	23.8	1318

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load