



7-30 Waters (Handgun)

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.550"	2.550"	2.550"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	CCI 200	31.0	2006	35.0	2294
IMR 4895	Federal	CCI 200	29.5	1964	33.5	2237
Vihtavuori N135	Federal	CCI 200	29.0	2002	33.0	2225
Hodgdon H4895	Federal	CCI 200	29.0	1947	33.0	2202
Accurate 2015	Federal	CCI 200	26.0	1908	30.0	2185
Hodgdon H335	Federal	CCI 250	28.0	1920	32.0	2094
IMR 3031	Federal	CCI 200	27.0	1808	31.0	2092
Winchester 748	Federal	CCI 250	30.0	1937	34.0	2066
Accurate 2230	Federal	CCI 200	24.0	1740	28.0	2034
Alliant Reloder 7	Federal	CCI 200	21.0	1726	25.0	1967

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load