



## 7mm Remington BR

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.235"	2.235"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4895	Remington	CCI 400	29.0	2167	<b>31.0 C</b>	2299
Winchester 748	Remington	CCI 450	31.0	2159	<b>33.0</b>	2295
IMR 4320	Remington	CCI 400	30.0	2125	<b>32.0</b>	2295
Hodgdon H335	Remington	CCI 400	28.5	2116	<b>30.5</b>	2289
Hodgdon H322	Remington	CCI 400	26.0	2059	<b>28.0 C</b>	2261
IMR 3031	Remington	CCI 400	27.0	2079	<b>29.0 C</b>	2242
Alliant Reloder 7	Remington	CCI 400	23.0	1901	<b>25.0</b>	2074

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*