



7mm Remington BR

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.225"	2.225"	2.225"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Remington	CCI 400	29.5	2187	31.5	2373
IMR 4320	Remington	CCI 400	29.0	2232	31.0 C	2333
Hodgdon BL-C(2)	Remington	CCI 400	28.0	2166	30.0	2324
Hodgdon H335	Remington	CCI 400	27.0	2096	29.0	2248
Winchester 748	Remington	CCI 450	30.0	2075	32.0 C	2228
Hodgdon H322	Remington	CCI 400	25.5	2069	27.5	2218
Alliant Reloder 7	Remington	CCI 400	22.5	1997	24.5	2193

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load