



7mm Remington BR

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	2.235"	2.235"	2.235"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Remington	CCI 400	27.5	2023	29.5 C	2209
IMR 4320	Remington	CCI 400	27.0	1977	29.0 C	2126
Hodgdon H335	Remington	CCI 400	26.0	1957	28.0	2123
Hodgdon BL-C(2)	Remington	CCI 400	26.0	1971	28.0	2116
Winchester 748	Remington	CCI 450	29.0	1983	31.0 C	2116
Hodgdon H322	Remington	CCI 400	24.5	1922	26.5	2072
Alliant Reloder 7	Remington	CCI 400	21.0	1830	23.0	2011

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load