

7mm T/CU

0.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	2.670"	2.670"	2.670"
Speer Part No.	1634	1635	1638

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H322	Federal	CCI 400	24.5	1838	26.5	1988
IMR 4895	Federal	CCI 400	25.5	1828	27.5	1971
Hodgdon H4895	Federal	CCI 400	25.5	1797	27.5 C	1938
Accurate 2460	Federal	CCI 400	25.5	1792	27.5	1932
IMR 3031	Federal	CCI 400	24.5	1770	26.5	1914
Winchester 748	Federal	CCI 400	27.0	1768	29.0	1899
Hodgdon H335	Federal	CCI 400	26.0	1754	28.0	1889
Hodgdon BL-C(2)	Federal	CCI 400	26.0	1745	28.0	1879
Accurate 2015	Federal	CCI 400	22.5	1725	24.5	1878
Vihtavuori N130	Federal	CCI 400	20.0	1615	22.0	1776
Alliant Reloder 7	Federal	CCI 400	18.5	1553	20.5	1721

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load