



218 Bee

<b>.224"</b>	<b>22</b>
<b>Weight (grains)</b>	<b>FNSP /cann</b>
<b>Ballistic Coefficient</b>	46
<b>Sectional Density</b>	0.087
<b>COAL Tested</b>	0.131
<b>Speer Part No.</b>	1.655"
	1024

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4198	Winchester	CCI 400	12.8	2466	14.2 C	2738
Hodgdon Lil' Gun	Winchester	CCI 400	9.5	2441	10.5	2662
Accurate 2460	Winchester	CCI 400	15.3	2365	17.0 C	2551
Accurate 1680	Winchester	CCI 400	10.8	2329	12.0	2517
Vihtavuori N110	Winchester	CCI 400	8.3	2224	9.2	2379
Ramshot Enforcer	Winchester	CCI 400	8.7	2234	9.4	2376
Winchester 296	Winchester	CCI 400	8.1	2161	9.0	2325
Accurate No. 9	Winchester	CCI 400	7.8	2082	8.7	2290
Hodgdon H110	Winchester	CCI 400	8.1	1959	9.0	2215
Alliant 2400	Winchester	CCI 400	7.5	1997	8.3	2151
IMR 4227	Winchester	CCI 400	8.9	1914	9.8	2127

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*