



22-250 Remington

.224"	22 HP	22 Match HP BT
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.148	0.148
COAL Tested	2.350"	2.350"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	30.6	3498	33.9	3755
Alliant Reloder 10X	Remington	CCI 200	29.0	3406	33.0	3744
IMR 3031	Remington	CCI 200	32.0	3251	36.0	3715
Winchester 748	Remington	CCI 250	34.0	3231	38.0	3714
Hodgdon H4895	Remington	CCI 200	32.5	3230	36.5	3713
Accurate 2460	Remington	CCI 250	32.5	3173	36.5	3711
Hodgdon Varget	Remington	CCI 200	32.0	3338	36.0	3706
Hodgdon H380	Remington	CCI 250	38.0	3164	42.0 C	3700
IMR 8208 XBR	Federal	Federal 210	29.5	3483	32.2	3680
Vihtavuori N140	Remington	CCI 200	33.5	3233	37.5	3674
Alliant Reloder 15	Remington	CCI 200	33.5	3204	37.5	3662
Vihtavuori N135	Remington	CCI 200	31.5	3177	35.5	3610
Winchester 760	Remington	CCI 250	36.5	3120	40.5	3607
Hodgdon H414	Remington	CCI 250	36.5	3093	40.5	3597
IMR 4064	Remington	CCI 200	32.5	3064	36.5	3563
IMR 4320	Remington	CCI 200	33.5	3150	37.5	3559
IMR 4895	Remington	CCI 200	31.0	3121	35.0	3526
Alliant Power Pro 1200-R	Federal	Federal 210	24.9	3174	27.6	3525

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load