



22-250 Remington

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	55	55
Ballistic Coefficient	0.212	0.233
Sectional Density	0.157	0.157
COAL Tested	2.350"	2.350"
Speer Part No.	1047	1032

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	Federal 210	32.9	3379	36.5	3712
Alliant AR-Comp	Federal	Federal 210	30.7	3432	34.0	3689
IMR 3031	Remington	CCI 200	32.0	3132	36.0	3663
Accurate 2460	Remington	CCI 250	32.0	3168	36.0	3662
Winchester 748	Remington	CCI 250	34.0	3237	38.0	3658
Hodgdon Varget	Remington	CCI 200	32.0	3260	36.0	3655
Hodgdon H380	Remington	CCI 250	38.0	3143	42.0 C	3633
Hodgdon H4895	Remington	CCI 200	32.0	3104	36.0	3630
IMR 8208 XBR	Federal	Federal 210	28.5	3301	31.6	3584
Vihtavuori N140	Remington	CCI 200	33.0	3134	37.0	3582
Hodgdon H335	Remington	CCI 250	32.0	3091	36.0	3532
Accurate 2520	Remington	CCI 250	30.0	2972	34.0	3476
IMR 4064	Remington	CCI 200	32.0	2999	36.0	3467
Winchester 760	Remington	CCI 250	35.5	2949	39.5	3449
IMR 4895	Remington	CCI 200	31.0	2993	35.0	3421
IMR 4350	Remington	CCI 200	36.0	3012	40.0 C	3403
IMR SR 4759 (reduced load)	Remington	CCI 200	11.0	1688	13.0	2002

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load