



220 Swift

.224"	22
Weight (grains)	Spire SP
Ballistic Coefficient	40
Sectional Density	0.144
COAL Tested	0.114
Speer Part No.	2.625"
	1017

NOTE: COAL is under minimum. May required single-loading in some rifles.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Hornady	CCI 200	39.1	3879	43.4	4253
Hodgdon Varget	Hornady	CCI 200	37.8	3866	41.8	4221
Alliant Reloder 17	Hornady	CCI 200	41.0	3830	44.4	4214
Alliant AR-Comp	Hornady	CCI 200	34.9	3867	38.6	4197
IMR 4451	Hornady	CCI 200	41.5	3705	44.5 C	3973
Alliant Reloder 16	Hornady	CCI 200	41.5	3769	43.5 C	3942
Hodgdon H380	Winchester	CCI 250	41.0	3588	45.0 C	3922
Alliant Reloder 15	Winchester	CCI 200	37.0	3513	41.0	3910
Vihtavuori N140	Winchester	CCI 200	36.0	3471	40.0	3860
Vihtavuori N160	Winchester	CCI 200	42.0	3440	46.0 C	3841
Winchester 760	Winchester	CCI 250	39.0	3433	43.0	3821
IMR 4350	Winchester	CCI 200	41.0	3363	45.0 C	3802
IMR 3031	Winchester	CCI 200	34.5	3445	38.5	3797
Accurate 4350	Winchester	CCI 200	41.0	3265	45.0 C	3691
Alliant Reloder 19	Winchester	CCI 200	42.0	3287	46.0 C	3671
IMR 4064	Winchester	CCI 200	35.0	3321	39.0	3642
IMR SR 4759 (reduced load)	Winchester	CCI 200	10.5	1662	12.5	1964

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load