



## 222 Remington

<b>.224"</b>	<b>22</b>	<b>22</b>
	<b>HP</b>	<b>Match BTHP</b>
<b>Weight (grains)</b>	52	52
<b>Ballistic Coefficient</b>	0.168	0.230
<b>Sectional Density</b>	0.148	0.148
<b>COAL Tested</b>	2.130"	2.130"
<b>Speer Part No.</b>	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2520	Remington	CCI 450	24.0	3003	<b>26.0 C</b>	3337
Vihtavuori N133	Remington	CCI 400	20.5	3077	<b>22.5 C</b>	3326
IMR 4895	Remington	CCI 400	22.5	3049	<b>24.5 C</b>	3279
Hodgdon H4895	Remington	CCI 400	22.0	3048	<b>24.0</b>	3277
Hodgdon H322	Remington	CCI 400	20.5	2979	<b>22.5</b>	3256
IMR 3031	Remington	CCI 400	21.5	3035	<b>23.5 C</b>	3246
Hodgdon BL-C(2)	Remington	CCI 450	23.5	2926	<b>25.5</b>	3233
Accurate 2460	Remington	CCI 450	21.5	2930	<b>23.5</b>	3185
Alliant Power Pro Varmint	Federal	Federal 205	22.2	2846	<b>24.7</b>	3163
Alliant Power Pro 1200-R	Federal	Federal 205	19.5	2860	<b>21.5</b>	3131
Alliant Reloder 7	Remington	CCI 400	18.0	2835	<b>20.0</b>	3115
Hodgdon CFE 223	Federal	Federal 205	22.7	2842	<b>25.2</b>	3114
Accurate 2230	Remington	CCI 450	21.0	2922	<b>23.0</b>	3109
Winchester 748	Remington	CCI 450	22.5	2904	<b>24.5</b>	3106
Alliant Reloder 10X	Federal	Federal 205	19.6	2820	<b>21.6</b>	3088
Hodgdon H4198	Remington	CCI 400	17.5	2917	<b>19.5</b>	3087
Accurate LT-30	Federal	Federal 205	18.6	2790	<b>20.7</b>	3079
Hodgdon H335	Remington	CCI 450	21.5	2880	<b>23.5</b>	3064
IMR 4198	Remington	CCI 400	17.5	2821	<b>19.5</b>	3050

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*