



## 222 Remington Magnum

.224"	22 HP	22 Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.147	0.147
COAL Tested	2.250"	2.250"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Remington	CCI 450	26.0	3232	<b>28.0</b>	3488
Hodgdon BL-C(2)	Remington	CCI 450	24.5	3187	<b>26.5</b>	3466
IMR 4320	Remington	CCI 400	27.0	3229	<b>29.0</b>	3454
IMR 3031	Remington	CCI 400	24.5	3177	<b>26.5</b>	3429
IMR 4064	Remington	CCI 400	26.0	3195	<b>28.0</b>	3423
IMR 4895	Remington	CCI 400	25.0	3104	<b>27.0</b>	3337
Hodgdon H414	Remington	CCI 450	29.0	3066	<b>31.0</b>	3301
Alliant Reloder 7	Remington	CCI 400	20.0	2935	<b>22.0</b>	3227

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*