



222 Remington

.224"	22
Weight (grains)	Spire SP
Ballistic Coefficient	40
Sectional Density	0.144
COAL Tested	0.114
Speer Part No.	2.040"
	1017

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Remington	CCI 400	20.0	3382	22.0	3617
Accurate 2015	Remington	CCI 400	22.0	3301	24.0	3608
Accurate 2460	Remington	CCI 450	23.5	3212	25.5 C	3581
Hodgdon H322	Remington	CCI 400	22.5	3273	24.5	3538
Alliant Power Pro 1200-R	Federal	Federal 205	21.3	3189	23.6	3505
Hodgdon BL-C(2)	Remington	CCI 450	24.5	3236	26.5 C	3502
Hodgdon H4198	Remington	CCI 400	19.5	3306	21.5	3498
Alliant Power Pro Varmint	Federal	Federal 205	24.0	3137	26.6	3486
Accurate 2230	Remington	CCI 450	22.5	3143	24.5	3465
Accurate 2520	Remington	CCI 450	24.0	3299	26.0 C	3447
IMR 4198	Remington	CCI 400	19.0	3237	21.0	3444
Accurate LT-30	Federal	Federal 205	20.0	3117	22.1	3441
Alliant Reloder 10X	Federal	Federal 205	21.1	3111	23.4	3439
IMR 4895	Remington	CCI 400	23.0	3157	25.0 C	3432
Winchester 748	Remington	CCI 450	23.0	3079	25.0	3402
Vihtavuori N120	Remington	CCI 400	18.0	3049	20.0	3395
Hodgdon H335	Remington	CCI 450	23.0	3078	25.0	3382
Hodgdon H4895	Remington	CCI 400	22.0	3000	24.0 C	3333
IMR 3031	Remington	CCI 400	22.0	3080	24.0 C	3312
Alliant AR-Comp	Federal	Federal 205	23.1	3167	24.0 C	3281

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load