



225 Winchester

.224"	22 HP	22 Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.23
Sectional Density	0.147	0.147
COAL Tested	2.500"	2.500"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Winchester	CCI 250	33.0	3170	37.0 C	3571
IMR 4064	Winchester	CCI 200	29.0	3134	33.0	3551
Winchester 748	Winchester	CCI 250	30.0	3075	34.0	3533
IMR 3031	Winchester	CCI 200	27.0	3059	31.0	3524
IMR 4350	Winchester	CCI 200	32.5	3122	36.5 C	3519
Hodgdon H380	Winchester	CCI 250	31.5	3096	35.5	3502
Hodgdon H322	Winchester	CCI 200	26.5	3018	30.5	3445
Hodgdon H414	Winchester	CCI 250	32.0	3047	36.0	3410
IMR 4895	Winchester	CCI 200	27.0	2915	31.0	3362

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load