



## 225 Winchester

.224"	22 TNT® HP	22 Spitzer SP
Weight (grains)	55	55
Ballistic Coefficient	0.233	0.212
Sectional Density	0.157	0.157
COAL Tested	2.500"	2.500"
Speer Part No.	1032	1047

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	28.5	3095	32.5	3503
Winchester 748	Winchester	CCI 250	29.5	3036	33.5	3424
Hodgdon H380	Winchester	CCI 250	31.0	3023	35.0	3414
IMR 4350	Winchester	CCI 200	32.0	3027	36.0 C	3397
Winchester 760	Winchester	CCI 250	32.0	3003	36.0	3359
Hodgdon H322	Winchester	CCI 200	26.0	2888	30.0	3318
Hodgdon H414	Winchester	CCI 250	31.0	2926	35.0	3279
IMR 4895	Winchester	CCI 200	26.5	2833	30.5	3251
IMR SR 4759 (reduced load)	Winchester	CCI 200	10.0	1679	12.0	2009

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*