

## 22 Hornet

.224"	22 Spire SP
Weight (grains)	40
Ballistic Coefficient	0.144
Sectional Density	0.114
COAL Tested	1.723"
Speer Part No.	1017

			START CHARGE		MAXIMUM CHARGE	
Propellant	Case	Primer	Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon Lil' Gun	Winchester	CCI 500	12.0	2936	13.0 C	3020
Winchester 296	Winchester	CCI 500	9.2	2639	10.2	2782
Acurate 1680	Winchester	CCI 500	12.4	2574	13.4 C	2757
Hodgdon H110	Winchester	CCI 500	9.2	2589	10.2	2730
IMR 4227	Winchester	CCI 500	10.5	2436	11.3 C	2619
Vihtavuori N110	Winchester	CCI 500	8.1	2407	9.1	2587
Alliant 2400	Winchester	CCI 500	8.1	2278	9.1	2557

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load