



22 PPC

.224"	22 TNT® HP	22 Spitzer SP
Weight (grains)	55	55
Ballistic Coefficient	0.233	0.212
Sectional Density	0.157	0.157
COAL Tested	2.080"	2.050"
Speer Part No.	1032	1047

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Sako	CCI BR4	26.0	3150	<b>28.0 C</b>	3392
Hodgdon H335	Sako	CCI BR4	26.0	3101	<b>28.0 C</b>	3339
Hodgdon H322	Sako	CCI BR4	25.0	3093	<b>27.0 C</b>	3322
Alliant Reloder 7	Sako	CCI BR4	22.0	3019	<b>24.0</b>	3277
Winchester 748	Sako	CCI BR4	27.5	2990	<b>29.5 C</b>	3228
IMR 4320	Sako	CCI BR4	26.0	2994	<b>28.0 C</b>	3203
IMR 4895	Sako	CCI BR4	25.0	2966	<b>27.0 C</b>	3186
IMR 4198	Sako	CCI BR4	21.0	2914	<b>23.0</b>	3174

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*