



240 Weatherby Magnum

.243"	6mm
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	85
Sectional Density	0.380
COAL Tested	0.206
Speer Part No.	3.060"
	1213

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Weatherby	CCI 250	49.0	3304	53.0 C	3473
Hodgdon H414	Weatherby	CCI 250	48.0	3161	52.0	3430
IMR 4350	Weatherby	CCI 250	47.5	3162	51.5	3417
Winchester 760	Weatherby	CCI 250	46.0	3071	50.0	3349
IMR 4064	Weatherby	CCI 250	40.0	2976	44.0	3242
Hodgdon H380	Weatherby	CCI 250	43.0	2949	47.0	3236

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load