



243 Winchester

.243"	6mm
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	100
Sectional Density	0.446
COAL Tested	0.242
Speer Part No.	2.625"
	1220

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	42.3	2847	46.8 C	3143
Alliant Power Pro 4000-MR	Federal	Federal 210	38.2	2789	42.4	3045
Alliant Reloder 17	Federal	Federal 210	36.3	2764	40.6	3030
Alliant Reloder 23	Federal	Federal 210	40.2	2850	43.7 C	3028
Alliant Reloder 16	Federal	Federal 210	35.1	2775	39.0	2986
Ramshot Hunter	Federal	Federal 210	38.0	2770	41.7	2982
Vihtavuori N560	Winchester	Federal 210	41.5	2736	45.5	2966
Alliant Reloder 22	Winchester	Federal 210	42.0	2773	46.0	2960
IMR 4831	Winchester	Federal 210	38.0	2659	42.0	2913
Alliant Reloder 19	Winchester	Federal 210	39.5	2731	43.5	2903
IMR 4350	Winchester	Federal 210	37.5	2643	41.5	2880
Hodgdon H4831SC	Winchester	Federal 210	40.0	2639	44.0	2874
Ramshot Magnum	Winchester	Federal 215	45.0	2673	49.0 C	2868
Hodgdon H414	Winchester	Federal 215	36.5	2602	40.5	2862
Winchester 760	Winchester	Federal 215	36.5	2558	40.5	2828
Accurate 4350	Winchester	Federal 210	37.0	2581	41.0	2802
Alliant Reloder 15	Winchester	Federal 210	30.0	2443	34.0	2691

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load