



243 Winchester

.243"	6mm
	TNT® HP
Weight (grains)	70
Ballistic Coefficient	0.279
Sectional Density	0.169
COAL Tested	2.625"
Speer Part No.	1206

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	42.0	3338	46.4 C	3623
Vihtavuori N540	Winchester	Federal 210	41.0	3237	45.0	3552
Alliant Reloder 17	Federal	Federal 210	40.7	3218	45.3	3552
IMR 4895	Winchester	Federal 210	39.0	3303	43.0	3540
Hodgdon H414	Winchester	Federal 215	45.0	3332	47.0	3520
Hodgdon Varget	Winchester	Federal 210	39.0	3236	43.0	3515
Winchester 760	Winchester	Federal 215	44.0	3195	48.0	3514
Ramshot Big Game	Winchester	Federal 215	42.0	3303	46.0	3508
Alliant Reloder 15	Winchester	Federal 210	39.5	3189	43.5	3506
Alliant Power Pro 2000-MR	Federal	Federal 210	37.7	3295	41.5	3492
IMR 4350	Winchester	Federal 210	44.5	3135	48.5	3461
Alliant AR-Comp	Federal	Federal 210	33.5	3242	37.1	3456
Hodgdon CFE 223	Federal	Federal 210	35.1	3216	38.8	3449
Alliant Reloder 10X	Winchester	Federal 210	32.5	3189	36.5	3421
Accurate 4064	Winchester	Federal 210	39.0	3089	43.0	3419
Alliant Power Pro Varmint	Federal	Federal 210	32.5	3137	36.1	3394

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load