



## 243 Winchester

<b>.243"</b>	<b>6mm Spitzer SP Hot- Cor®</b>
<b>Weight (grains)</b>	90
<b>Ballistic Coefficient</b>	0.365
<b>Sectional Density</b>	0.218
<b>COAL Tested</b>	2.625"
<b>Speer Part No.</b>	1217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 4000-MR	Federal	Federal 210	39.6	2947	43.8	3203
Vihtavuori N560	Winchester	Federal 210	45.0	2880	49.0 C	3175
Alliant Reloder 17	Federal	Federal 210	37.3	2914	41.3	3170
Alliant Reloder 16	Federal	Federal 210	37.4	2934	41.5	3163
IMR 4350	Winchester	Federal 210	41.0	2877	45.0	3149
Hodgdon H4350	Winchester	Federal 210	40.0	2853	44.0	3132
Hodgdon H414	Winchester	Federal 215	39.5	2830	43.5	3126
Ramshot Big Game	Winchester	Federal 215	37.5	2856	41.5	3084
Accurate 4350	Winchester	Federal 210	41.5	2805	45.5 C	3080
Alliant Reloder 19	Winchester	Federal 210	43.0	2879	47.0 C	3079
IMR 4895	Winchester	Federal 210	35.0	2826	39.0	3071
Hodgdon H4831SC	Federal	Federal 210	37.5	2861	41.1	3070
Alliant Power Pro 2000-MR	Federal	Federal 210	34.5	2837	38.2	3063
Hodgdon 760	Winchester	Federal 215	39.0	2749	43.0	3056
Alliant Reloder 22	Winchester	Federal 210	44.0	2837	48.0 C	3053
Alliant Reloder 15	Winchester	Federal 210	34.0	2767	38.0	3020
Accurate 5744 (reduced load)	Winchester	Federal 210	21.0	2105	23.0	2273

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load