



25-06 Remington

.257"	25 Spitzer SP Hot- Cor®	25 TNT® HP
Weight (grains)	87	87
Ballistic Coefficient	0.300	0.337
Sectional Density	0.188	0.188
COAL Tested	3.115"	3.115"
Speer Part No.	1241	1246

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N560	Winchester	CCI 200	53.0	3353	57.0	3552
Alliant Reloder 19	Winchester	CCI 200	56.0	3089	60.0 C	3452
Alliant Power Pro 4000-MR	Federal	Federal 210	51.0	3166	55.5	3434
Hodgdon H4350	Winchester	CCI 200	54.0	3157	58.0	3431
IMR 4831	Winchester	CCI 200	55.0	3102	59.0	3428
IMR 7828	Winchester	CCI 200	59.0	3076	63.0 C	3419
Hodgdon H4831SC	Winchester	CCI 200	55.5	3298	57.5	3410
IMR 4350	Winchester	CCI 200	52.0	3075	56.0	3380
Hodgdon H414	Winchester	CCI 250	47.0	3077	51.0	3359
Accurate 3100	Winchester	CCI 200	57.0	3021	61.0 C	3357
IMR 4064	Winchester	CCI 200	45.0	3083	49.0	3352
Alliant AR-Comp	Federal	Federal 210	39.5	3055	43.4	3278
Hodgdon H380	Winchester	CCI 250	48.0	2940	52.0	3268
Alliant Reloder 15	Winchester	CCI 200	43.0	2983	47.0	3268
Alliant Power Pro Varmint	Federal	Federal 210	33.5	2846	36.9	3078
IMR SR 4759 (reduced load)	Winchester	CCI 200	13.0	1502	17.0	1933

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load