



250 Savage

.257"	25 Spitzer SP Hot- Cor®	25 HP	25 Spitzer BTSP
Weight (grains)	100	100	100
Ballistic Coefficient	0.334	0.263	0.393
Sectional Density	0.216	0.216	0.216
COAL Tested	2.450"	2.400"	2.490"
Speer Part No.	1405	1407	1408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE 223	Hornady	CCI 200	36.0	2877	38.2	3026
Alliant Power Pro Varmint	Hornady	CCI 200	33.0	2792	35.4	2954
IMR 4451	Hornady	CCI 200	36.0	2629	38.7	2791
IMR 4166	Hornady	CCI 200	30.5	2640	32.7	2783
Accurate 2520	Winchester	CCI 250	29.0	2392	33.0	2763
Hodgdon H414	Winchester	CCI 250	34.0	2504	38.0 C	2743
Winchester 760	Winchester	CCI 250	34.0	2480	38.0 C	2716
Hodgdon H4350	Winchester	CCI 200	34.0	2340	38.0 C	2674
Accurate 3100	Winchester	CCI 200	36.0	2340	40.0 C	2670
Winchester 748	Winchester	CCI 250	30.0	2294	34.0	2649
IMR 4350	Winchester	CCI 200	33.5	2313	37.5 C	2647
IMR 4831	Winchester	CCI 200	35.0	2301	39.0 C	2633
IMR 4064	Winchester	CCI 200	29.0	2346	33.0	2622
Hodgdon H380	Winchester	CCI 250	31.0	2256	35.0	2604
Alliant Reloder 15	Winchester	CCI 200	28.0	2244	32.0	2532
Hodgdon BL-C(2)	Winchester	CCI 250	28.0	2223	32.0	2509

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load