



## 257 Roberts +P

.257"	25 Spitzer SP Hot- Cor®	25 HP	25 Spitzer BTSP
Weight (grains)	100	100	100
Ballistic Coefficient	0.334	0.263	0.393
Sectional Density	0.126	0.216	0.126
COAL Tested	2.770"	2.760"	2.770"
Speer Part No.	1405	1407	1408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Winchester	CCI 250	41.0	2804	45.0	3113
Alliant Reloder 16	Federal	Federal 210	41.3	2822	45.8 C	3110
Alliant Reloder 19	Winchester	CCI 200	45.0	2843	49.0	3094
Ramshot Hunter	Federal	Federal 210	45.2	2946	48.0	3091
Alliant Power Pro 4000-MR	Federal	Federal 210	42.2	2775	46.8 C	3069
Alliant Reloder 23	Federal	Federal 210	44.0	2773	48.8 C	3064
Hodgdon H4350	Winchester	CCI 200	43.0	2795	47.0 C	3055
IMR 4831	Winchester	CCI 200	44.0	2805	48.0	3053
Alliant Reloder 17	Federal	Federal 210	42.0	2843	45.1	3050
Hodgdon H4831	Winchester	CCI 200	46.0	2774	50.0 C	3030
IMR 7828	Winchester	CCI 200	47.0	2711	51.0 C	3023
IMR 4350	Winchester	CCI 200	41.0	2694	45.0	2944
Hodgdon H414	Winchester	CCI 250	40.0	2657	44.0	2878
IMR 4064	Winchester	CCI 200	35.0	2584	39.0	2871
Hodgdon H380	Winchester	CCI 250	38.0	2566	42.0	2842
Accurate 2700	Winchester	CCI 250	37.0	2529	41.0	2807
Alliant Reloder 15	Winchester	CCI 200	33.0	2509	37.0	2785
IMR 4320	Winchester	CCI 200	35.0	2505	39.0	2768
IMR SR 4759 (reduced load)	Winchester	CCI 200	15.0	1728	17.0	1945

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load