



257 Roberts +P

.257"	25 Spitzer SP Hot- Cor®	25 TNT® HP
Weight (grains)	87	87
Ballistic Coefficient	0.300	0.337
Sectional Density	0.188	0.188
COAL Tested	2.760"	2.780"
Speer Part No.	1241	1246

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder® 16	Federal®	Federal 210	44.9	3064	49.6 C	3386
Hodgdon H4350	Winchester	CCI 200	47.0	3161	51.0 C	3381
Ramshot Hunter	Federal	Federal 210	46.7	3121	51.6	3367
Alliant Power Pro® 2000-MR	Federal	Federal 210	41.6	2993	46.2	3295
Alliant Power Pro 4000-MR	Federal	Federal 210	44.8	2994	49.6 C	3294
Alliant Reloder 17	Federal	Federal 210	43.6	2940	48.4	3290
IMR 4831	Winchester	CCI 200	47.0	2993	51.0	3226
Alliant Reloder 19	Winchester	CCI 200	47.0	2947	51.0 C	3187
IMR 7828	Winchester	CCI 200	50.0	2955	54.0	3184
Hodgdon H380	Winchester	CCI 250	42.0	2884	46.0	3170
Winchester 760	Winchester	CCI 250	43.0	2868	47.0	3163
Accurate 3100	Winchester	CCI 200	48.0	2925	52.0 C	3153
Alliant Reloder 15	Winchester	CCI 200	39.0	2804	43.0	3129
IMR 4350	Winchester	CCI 200	43.0	2876	47.0	3069
Winchester 748	Winchester	CCI 250	39.0	2735	43.0	3056
Hodgdon H414	Winchester	CCI 250	42.0	2726	46.0	3009
IMR SR 4759 (reduced load)	Winchester	CCI 200	15.0	1762	17.0	2008

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load