



25 Winchester Super Short Magnum

.257"	25 Spitzer SP Hot- Cor®	25 HP	25 Spitzer BTSP
Weight (grains)	100	100	100
Ballistic Coefficient	0.334	0.263	0.393
Sectional Density	0.216	0.216	0.216
COAL Tested	2.270"	2.280"	2.270"
Speer Part No.	1405	1407	1408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Winchester	CCI 250	45.5	2995	49.5	3254
Hodgdon H414	Winchester	CCI 250	44.5	2991	48.5	3222
Accurate 4350	Winchester	CCI 200	44.0	2954	48.0 C	3200
Alliant Reloder 19	Winchester	CCI 200	45.5	2927	49.5 C	3180
Vihtavuori N560	Winchester	CCI 200	46.0	2891	50.0 C	3154
Ramshot Big Game	Winchester	CCI 250	42.0	2924	46.0	3141
IMR 4350	Winchester	CCI 200	43.0	2909	47.0 C	3137
Hodgdon H380	Winchester	CCI 250	41.5	2890	45.5	3135
Alliant Reloder 15	Winchester	CCI 200	37.5	2890	41.5	3110
Hodgdon Varget	Winchester	CCI 200	36.0	2886	40.0	3099
IMR 4895	Winchester	CCI 200	36.0	2845	40.0	3084
Alliant Reloder 10X	Winchester	CCI 200	31.0	2751	35.0	2984
Accurate 5744 (reduced load)	Winchester	CCI 200	20.0	1996	22.0	2136

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load