



25 Winchester Super Short Magnum

.257"	25
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	120
Sectional Density	0.480
COAL Tested	0.260
Speer Part No.	2.270"
	1410

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Winchester	CCI 250	41.0	2709	45.0	2929
Winchester 760	Winchester	CCI 250	41.0	2713	45.0	2921
Alliant Reloder 19	Winchester	CCI 200	42.0	2685	46.0 C	2914
Vihtavuori N560	Winchester	CCI 200	42.0	2662	46.0	2901
IMR 4350	Winchester	CCI 200	39.0	2624	43.0	2881
Accurate 4350	Winchester	CCI 200	39.0	2649	43.0	2861
Hodgdon H380	Winchester	CCI 250	38.5	2624	42.5	2846
Ramshot Big Game	Winchester	CCI 250	38.0	2622	42.0	2840
Alliant Reloder 15	Winchester	CCI 200	34.0	2551	38.0	2792
IMR 4895	Winchester	CCI 200	33.0	2528	37.0	2776
Hodgdon Varget	Winchester	CCI 200	32.5	2522	36.5	2744
Alliant Reloder 10X	Winchester	CCI 200	27.5	2368	31.5	2607

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load