



## 260 Remington

<b>.264"</b>	<b>6.5mm</b>
	<b>Spitzer SP</b>
<b>Weight (grains)</b>	140
<b>Ballistic Coefficient</b>	0.498
<b>Sectional Density</b>	0.287
<b>COAL Tested</b>	2.745"
<b>Speer Part No.</b>	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Remington	CCI 200	43.5	2603	<b>45.5C</b>	2731
IMR 4831	Remington	CCI 200	42.0	2587	<b>44.0 C</b>	2722
Alliant Reloder 22	Remington	CCI 200	44.0	2554	<b>46.0 C</b>	2701
Alliant Reloder 23	Federal	Federal 210	38.7	2514	<b>42.7</b>	2696
Alliant Power Pro 4000-MR	Federal	Federal 210	37.0	2509	<b>40.4</b>	2696
Accurate 4350	Remington	CCI 200	41.0	2540	<b>43.0 C</b>	2695
Vihtavuori N165	Remington	CCI 200	45.0	2568	<b>47.0 C</b>	2687
IMR 4350	Remington	CCI 200	41.0	2522	<b>43.0 C</b>	2687
Alliant Reloder 17	Federal	Federal 210	36.0	2506	<b>39.0</b>	2678
Hodgdon H4831SC	Remington	CCI 200	43.5	2531	<b>45.5 C</b>	2635
Alliant Reloder 16	Federal	Federal 210	34.8	2443	<b>38.4</b>	2635
Winchester 760	Remington	CCI 250	39.5	2528	<b>41.5</b>	2623
Accurate 3100	Remington	CCI 200	43.0	2542	<b>45.0 C</b>	2614
Hodgdon H4350	Federal	Federal 210	34.7	2413	<b>38.4</b>	2614
Hodgdon H414	Remington	CCI 250	39.5	2519	<b>41.5</b>	2596
IMR 4064	Remington	CCI 200	35.0	2460	<b>37.0</b>	2572
Accurate 5744 (reduced load)	Remington	CCI 200	22.0	1894	<b>24.0</b>	2021

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*