



270 Winchester

.277"	270
	HP
Weight (grains)	100
Ballistic Coefficient	0.201
Sectional Density	0.186
COAL Tested	3.100"
Speer Part No.	1447

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	55.1	3289	60.8 C	3557
Hodgdon Varget	Winchester	CCI 200	51.0	3237	55.0	3497
Alliant Reloder 17	Federal	Federal 210	53.0	3152	58.6	3496
Accurate 4350	Winchester	CCI 200	57.0	3267	61.0 C	3474
Alliant Power Pro 2000-MR	Federal	Federal 210	49.9	3207	54.6	3438
IMR 4350	Winchester	CCI 200	57.0	3182	61.0 C	3414
Alliant AR-Comp	Federal	Federal 210	45.4	3153	50.2	3404
Hodgdon H414	Winchester	CCI 250	55.0	3203	59.0	3404
IMR 8208 XBR	Federal	Federal 210	44.1	3207	48.1	3356
Winchester 760	Winchester	CCI 250	54.0	3162	58.0	3345
IMR 4320	Winchester	CCI 200	49.0	3068	53.0	3343
Alliant Power Pro Varmint	Federal	Federal 210	44.8	3146	48.7	3330
Alliant Reloder 19	Winchester	CCI 200	58.0	3034	62.0 C	3273
Vihtavuori N140	Winchester	CCI 200	47.0	2993	51.0	3272
IMR 4064	Winchester	CCI 200	48.0	2994	52.0	3262
Hodgdon H380	Winchester	CCI 250	51.0	2998	55.0	3249
IMR 4895	Winchester	CCI 200	46.0	3126	50.0	3220
Accurate 3100	Winchester	CCI 250	58.0	2979	62.0 C	3214
IMR SR 4759 (reduced load)	Winchester	CCI 200	16.0	1545	20.0	1923

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load