



## 270 Winchester

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®	270 Grand Slam® SP/CANN
Weight (grains)	130	130	130
Ballistic Coefficient	0.412	0.383	0.332
Sectional Density	0.242	0.242	0.242
COAL Tested	3.240"	3.200"	3.240"
Speer Part No.	1458	1459	1465

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	54.3	2878	60.3	3171
Hodgdon H1000	Winchester	CCI 250	60.0	2825	64.0	3166
Alliant Reloder 23	Federal	Federal 210	52.9	2854	58.6 C	3113
IMR 7828	Winchester	CCI 250	58.0	2858	62.0	3113
Alliant Reloder 17	Federal	Federal 210	48.7	2836	54.0	3102
Alliant Power Pro 4000-MR	Federal	Federal 210	50.4	2834	55.8	3092
Alliant Reloder 16	Federal	Federal 210	48.3	2843	53.5	3088
Winchester 760	Winchester	CCI 250	50.0	2838	54.0	3052
IMR 4831	Winchester	CCI 200	54.0	2731	58.0	3014
Hodgdon H4350	Winchester	CCI 200	52.0	2767	56.0	2991
Alliant Reloder 22	Winchester	CCI 200	54.0	2722	58.0	2989
Vihtavuori N160	Winchester	CCI 200	51.5	2750	55.5	2971
Hodgdon H414	Winchester	CCI 250	50.0	2753	54.0	2961
IMR 4350	Winchester	CCI 200	51.0	2912	55.0	2948
Alliant Reloder 19	Winchester	CCI 200	53.0	2732	57.0	2944
Accurate 3100	Winchester	CCI 250	52.0	2577	56.0	2860
IMR 4064	Winchester	CCI 200	43.0	2657	47.0	2838
Alliant Reloder 15	Winchester	CCI 200	41.0	2576	45.0	2777
IMR SR 4759 (reduced load)	Winchester	CCI 200	20.0	1651	24.0	2008

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load