



270 Winchester

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®	270 Grand Slam® SP/CANN
Weight (grains)	150	150	150
Ballistic Coefficient	0.489	0.455	0.378
Sectional Density	0.279	0.279	0.279
COAL Tested	3.270"	3.210"	3.250"
Speer Part No.	1604	1605	1608

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 7828	Winchester	CCI 250	54.0	2727	58.0 C	2948
Alliant Reloder 26	Federal	Federal 210	51.5	2701	56.8	2943
Winchester 760	Winchester	CCI 250	49.0	2665	53.0	2913
Accurate 3100	Winchester	CCI 200	53.0	2675	57.0	2906
Alliant Reloder 23	Federal	Federal 210	49.7	2670	54.7 C	2874
IMR 4831	Winchester	CCI 200	51.0	2636	55.0	2870
Alliant Power Pro 4000-MR	Federal	Federal 210	47.7	2647	52.9	2867
Alliant Reloder 17	Federal	Federal 210	45.9	2637	50.8	2867
Hodgdon H4831SC	Winchester	CCI 200	53.5	2669	57.5	2860
Alliant Reloder 16	Federal	Federal 210	45.5	2631	50.4	2844
Alliant Reloder 22	Winchester	CCI 200	50.0	2590	54.0	2805
Alliant Reloder 19	Winchester	CCI 200	49.0	2593	53.0	2780
IMR 4350	Winchester	CCI 200	48.0	2560	52.0	2761
Hodgdon H414	Winchester	CCI 250	46.0	2513	50.0	2712
Vhtavuori N160	Winchester	CCI 200	47.0	2490	51.0	2702
Hodgdon H4350	Winchester	CCI 200	47.0	2481	51.0	2675
IMR 4064	Winchester	CCI 200	41.0	2477	45.0	2666
IMR SR 4759(reduced load)	Winchester	CCI 200	22.0	1655	26.0	1966

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load