



270 Winchester Short Magnum

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®	270 Grand Slam® SP
Weight (grains)	130	130	130
Ballistic Coefficient	0.412	0.383	0.332
Sectional Density	0.242	0.242	0.242
COAL Tested	2.700"	2.700"	2.670"
Speer Part No.	1458	1459	1465

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	61.5	2928	68.1	3289
IMR 7828	Winchester	CCI 200	62.0	3105	66.0	3250
Alliant Reloder 19	Winchester	CCI 200	62.0	3097	66.0	3241
Alliant Reloder 23	Federal	Federal 215	60.1	2955	66.1 C	3235
Alliant Power Pro 4000-MR	Federal	Federal 215	57.9	2935	63.9	3233
Alliant Reloder 22	Winchester	CCI 200	62.0	3096	66.0	3228
IMR 4831	Winchester	CCI 200	58.0	3067	62.0	3226
Alliant Reloder 16	Federal	Federal 215	56.5	2949	62.5	3224
Alliant Reloder 17	Federal	Federal 215	55.4	2996	61.4	3223
Hodgdon H1000	Federal	Federal 215	65.0	2964	71.8 C	3219
Accurate 3100	Winchester	CCI 200	62.0	3039	66.0	3213
IMR 4350	Winchester	CCI 200	56.0	3026	60.0	3183
Hodgdon H4831SC	Winchester	CCI 200	59.0	3035	63.0	3173
Ramshot Hunter	Federal	Federal 215	57.3	2916	63.3	3168
Hodgdon H4350	Winchester	CCI 200	54.0	3013	58.0	3163
Vihavouri N160	Federal	Federal 215	58.1	2781	64.1	3120
Accurate 5744 (reduced load)	Winchester	CCI 200	25.0	1940	27.0	2048

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load