



270 Winchester Short Magnum

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®	270 Grand Slam® SP
Weight (grains)	150	150	150
Ballistic Coefficient	0.489	0.455	0.378
Sectional Density	0.279	0.279	0.279
COAL Tested	2.700"	2.670"	2.700"
Speer Part No.	1604	1605	1608

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	58.3	2787	64.9 C	3093
Ramshot Magnum	Federal	Federal 215	63.6	2813	69.7 C	3093
Alliant Reloder 25	Winchester	CCI 200	60.0	2882	64.0	3058
Alliant Power Pro 4000-MR	Federal	Federal 215	55.1	2768	61.1 C	3041
Alliant Reloder 23	Federal	Federal 215	57.0	2773	63.1 C	3037
Hodgdon H1000	Federal	Federal 215	61.2	2824	67.8 C	3037
IMR 7828	Winchester	CCI 200	58.0	2796	62.0	3011
Alliant Reloder 22	Winchester	CCI 200	57.0	2839	61.0	3009
Vihavouri N165	Federal	Federal 215	60.2	2682	66.9 C	3007
Alliant Reloder 17	Federal	Federal 215	51.1	2748	56.5	2994
Alliant Reloder 19	Winchester	CCI 200	56.0	2831	60.0	2990
IMR 4831	Winchester	CCI 200	54.0	2774	58.0	2959
Hodgdon H4831SC	Winchester	CCI 200	56.0	2776	60.0	2959
IMR 4350	Winchester	CCI 200	51.0	2757	55.0	2930
Accurate 3100	Winchester	CCI 200	56.0	2796	60.0	2848

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load